



en ENGLISH

NOTE: IF YOUR EYES ARE NOT PARALLEL, AS IN THE CASE OF HETEROPHORIA, YOU MAY NEED TO SIGHT WITH ONE EYE. CHECK BY FIRST TAKING A READING WITH BOTH EYES OPEN, THEN CLOSE THE EYE LOOKING AT THE OBJECT. IF YOUR READING CHANGES SIGNIFICANTLY, USE JUST ONE EYE TO SIGHT OBJECT AND TAKE READING.

TECHNICAL SPECIFICATIONS

- Operating temperature: -30°C ... +60°C / -22°F ... +140°F
- Storage temperature: -30°C ... +60°C / -22°F ... +140°F
- KB-14**
- Weight: 93g
- Dimensions: 74 x 52 x 15 mm / 2 3/4" x 2" x 5/8".
- Scales and resolutions: One or two of the following scales are implemented depending on the model; not all combinations are available.
 - Scale: 360°, resolution ½°
 - Scale: reversed 360°, resolution ½°
 - Scale: quadrant degrees, resolution ¼°
 - Scale: 400 g, resolution 1 g
 - Scale: 6400 mils, resolution 10 mils.
- Accuracy: 1/3"
- PM-5**
- Weight: 94 g / 3.3 oz.
- Dimensions: 74 x 52 x 15 mm / 2 3/4" x 2" x 5/8".
- Scales and resolutions: Two to three of the following scales are implemented depending on model; not all combinations are available.
 - Scale: 0 to ±35mm (15m distance scale), resolution ¼-½m depending on reading
 - Scale: 0 to ±50mm (20m distance scale), resolution ¼-½m depending on reading
 - Scale: 0 to ±200' (66' distance scale), resolution 1-5' depending on reading
 - Scale: 0 to ±90°, resolution 1°
 - Scale: 0 to ±150%, resolution 1-2% depending on reading
 - Scale: 0 to ±100g, resolution 1 g
 - Scale: 0 to ±1600 mils, resolution 10 mils
 - Scale: 1 to 5 secant (note that reading is secant x 100), resolution 0.5 seconds to 1 second depending on reading
- Accuracy: height scales ±2%, clinometer scales ¼"
- Tandem**
- Weight: 177g
- Dimensions: 126 x 76 x 15 mm
- Scales, resolutions and accuracy: see KB-14 and PM-5

INTERNATIONAL LIMITED WARRANTY

Suunto warrants that during the Warranty Period Suunto or a Suunto Authorized Service Center (hereinafter Service Center) will, at its sole discretion, remedy defects in materials or workmanship free of charge either by a) repairing, b) replacing, or c) refunding, subject to the terms and conditions of this International Limited Warranty. This International Limited Warranty is valid and enforceable regardless of the country of purchase. The International Limited Warranty does not affect your legal rights, granted under mandatory national law applicable to the sale of consumer goods.

Warranty Period

The International Limited Warranty Period starts at the date of original retail purchase. The Warranty Period is two (2) years for Products and Dive transmitters unless otherwise specified.

The Warranty Period is one (1) year for accessories including but not limited to wireless sensors and transmitters, chargers, cables, rechargeable batteries, straps, bracelets and hoses.

Exclusions and Limitations

This International Limited Warranty does not cover:

1. a) normal wear and tear such as scratches, abrasions, or alteration of the color and/or material of non-metallic straps; b) defects caused by rough handling, or c) defects or damage resulting from use contrary to intended or recommended use, improper care, negligence, and accidents such as dropping or crushing;
2. printed materials and packaging;
3. defects or alleged defects caused by use with any product, accessory, software and/or service not manufactured or supplied by Suunto;
4. non-rechargeable batteries.

Suunto does not warrant that the operation of the Product or accessory will be uninterrupted or error free, or that the Product or accessory will work with any hardware or software provided by a third party.

This International Limited Warranty is not enforceable if the Product or accessory: 1. has been opened beyond intended use;

2. has been repaired using unauthorized spare parts; modified or repaired by unauthorized Service Center;

3. serial number has been removed, altered or made illegible in any way, as determined at the sole discretion of Suunto; or

4. has been exposed to chemicals including but not limited to sunscreen and mosquito repellents.

Access to Suunto warranty service

You must provide proof of purchase to access Suunto warranty service. You must also register your product online at www.suunto.com/mysuunto in order to be eligible to international warranty services globally. For instructions how to obtain warranty service, visit www.suunto.com/warranty, contact your local authorized Suunto retailer, or call Suunto Contact Center.

Limitation of Liability

To the maximum extent permitted by applicable mandatory laws, this International Limited Warranty is your sole and exclusive remedy and is in lieu of all other warranties, expressed or implied. Suunto shall not be liable for special, incidental, punitive or consequential damages, including but not limited to loss of anticipated benefits, loss of data, loss of use, cost of capital, cost of any substitute equipment or facilities, claims of third parties, damage to property resulting from the purchase or use of the item or arising from breach of the warranty, breach of contract, negligence, strict tort, or any legal or equitable theory, even if Suunto knew of the likelihood of such damages. Suunto shall not be liable for delay in rendering warranty service.

zh 简体中文

注意: 如果您的眼睛不平行（例如斜视），则需要使用一只眼睛观察。首先睁开双眼获取读数以进行检查。然后闭上一只眼睛观察物体。如果读数变化太大，则只使用一只眼睛观察物体并获取读数。

技术规格

- 工作温度: -30°C ... +60°C / -22°F ... +140°F
- 存放温度: -30°C ... +60°C / -22°F ... +140°F
- KB-14**
- 重量: 93克
- 尺寸: 74 x 52 x 15 mm / 2 3/4" x 2" x 5/8"。
- 刻度和分辨率: 取决于型号而定, 使用下列一种或两种刻度; 并非所有组合均可用。
 - 刻度: 360°, 分辨率 ½°
 - 刻度: 向反360°, 分辨率 ½°
 - 刻度: 角度角, 分辨率 ¼°
 - 刻度: 400 g, 分辨率 1 g
 - 刻度: 6400 mils, 分辨率 10 mils.
- 精确度: 1/3"
- PM-5**
- 重量: 94 克 / 3.3 盎司。
- 尺寸: 74 x 52 x 15 mm / 2 3/4" x 2" x 5/8"。
- 刻度和分辨率: 取决于型号而定, 使用下列一种或三种刻度; 并非所有组合均可用。
 - 刻度: 0 到 ±35mm (15m 距离刻度), 分辨率 ¼-½m
 - 刻度: 0 到 ±50mm (20m 距离刻度), 分辨率 ¼-½m
 - 刻度: 0 到 ±200' (66' 距离刻度), 分辨率 1-5' depending on reading
 - 刻度: 0 到 ±90°, 分辨率 1°
 - 刻度: 0 到 ±150%, 分辨率 1-2% depending on reading
 - 刻度: 0 到 ±100g, 分辨率 1 g
 - 刻度: 0 到 ±1600 mils, 分辨率 10 mils
 - 刻度: 1 到 5 秒 (注意: 读数为正割 x 100), 分辨率 0.5 秒 to 1 second depending on reading
- 精确度: 高度刻度 ±2%, 倾斜刻度 ¼"
- Tandem**
- 重量: 177 克
- 尺寸: 126 x 76 x 15 mm
- 刻度和分辨率: 参见 KB-14 和 PM-5

保修期

您必须提供购买证明才能使用 Suunto 保修服务。您还必须在 www.suunto.com/mysuunto 上注册自己的产品，以便在全球获得保修服务的说明。请访问 www.suunto.com/warranty、联系您的当地授权 Suunto 零售商，或者致电 Suunto 客户服务中心。

SUUNTO CUSTOM SUPPORT

- 1. www.suunto.com/support
- 2. AUSTRALIA (24/7) +61 1800 240 498
- AUSTRIA +43 720 883 104
- CANADA (24/7) +1 855 624 9080
- CHINA +86 400 661 1646
- CHINA - Hong Kong +852 58060687
- FINLAND +358 9 4245 0127
- FRANCE +33 4 81 68 09 26
- GERMANY +49 89 3803 8778
- ITALY +39 02 9475 1965
- JAPAN +81 3 4520 9417
- NETHERLANDS +31 1 0713 7269
- NEW ZEALAND (24/7) +64 9887 5223
- RUSSIA +7 499 918 7148
- SPAIN +34 91 11 43 175
- SWEDEN +46 8 5205 0730
- SWITZERLAND +41 44 580 9988
- UK (24/7) +44 20 3608 0534
- USA (24/7) +1 855 258 0900
- ▪ ▪

SUUNTO

© Suunto Oy 2013/2013, 3/2014, 6/2014, 11/2014, 3/2015, 2/2017. All rights reserved.

Suunto is a registered trademark of Suunto Oy.

• 尺寸: 126 x 76 x 15 mm
• 刻度、分辨率和精确度: 参见 KB-14 和 PM-5

国际有限保修

Suunto 保证，在保修期内，Suunto 或 Suunto 授权服务中心（以下简称“服务中心”）有权在本国际有限保修的条款和条件限制范围内，单方面酌情选择下列方式之一维修：a) 维修, b) 更换, 或者 c) 退款。无论产品购买于哪个国家/地区，本国际有限保修均有效并具有强制效力。本国际有限保修不给予消费者任何法律权利。

保修期限

本国际有限保修期限自原始零售购买之日起计算。除非另有规定，否则产品和潜水无线传感器的保修期限为两年（2年）。

KB-14

• 重量: 93g

• 尺寸: 74 x 52 x 15 mm / 2 3/4" x 2" x 5/8"。

• 刻度和分辨率: 两到三种刻度可供选择，取决于型号而定，而非所有组合均可用。

• 刻度: 360°, 分辨率 ½°

• 刻度: 向反360°, 分辨率 ½°

• 刻度: 角度角, 分辨率 ¼°

• 刻度: 400 g, 分辨率 1 g

• 刻度: 6400 mils, 分辨率 10 mils.

• 精确度: 1/3"

• 刻度: 0 到 ±35mm (15m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±50mm (20m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±200' (66' 距离刻度), 分辨率 1-5'

• 刻度: 0 到 ±90°, 分辨率 1°

• 刻度: 0 到 ±150%, 分辨率 1-2%

• 刻度: 0 到 ±100g, 分辨率 1 g

• 刻度: 0 到 ±1600 mils, 分辨率 10 mils

• 刻度: 1 到 5 秒 (注意: 读数为正割 x 100), 分辨率 0.5 秒 to 1 second depending on reading

• 精确度: 高度刻度 ±2%, 倾斜刻度 ¼"

• 刻度: 0 到 ±35mm (15m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±50mm (20m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±200' (66' 距离刻度), 分辨率 1-5'

• 刻度: 0 到 ±90°, 分辨率 1°

• 刻度: 0 到 ±150%, 分辨率 1-2%

• 刻度: 0 到 ±100g, 分辨率 1 g

• 刻度: 0 到 ±1600 mils, 分辨率 10 mils

• 刻度: 1 到 5 秒 (注意: 读数为正割 x 100), 分辨率 0.5 秒 to 1 second depending on reading

• 精确度: 高度刻度 ±2%, 倾斜刻度 ¼"

• 刻度: 0 到 ±35mm (15m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±50mm (20m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±200' (66' 距离刻度), 分辨率 1-5'

• 刻度: 0 到 ±90°, 分辨率 1°

• 刻度: 0 到 ±150%, 分辨率 1-2%

• 刻度: 0 到 ±100g, 分辨率 1 g

• 刻度: 0 到 ±1600 mils, 分辨率 10 mils

• 刻度: 1 到 5 秒 (注意: 读数为正割 x 100), 分辨率 0.5 秒 to 1 second depending on reading

• 精确度: 高度刻度 ±2%, 倾斜刻度 ¼"

• 刻度: 0 到 ±35mm (15m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±50mm (20m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±200' (66' 距离刻度), 分辨率 1-5'

• 刻度: 0 到 ±90°, 分辨率 1°

• 刻度: 0 到 ±150%, 分辨率 1-2%

• 刻度: 0 到 ±100g, 分辨率 1 g

• 刻度: 0 到 ±1600 mils, 分辨率 10 mils

• 刻度: 1 到 5 秒 (注意: 读数为正割 x 100), 分辨率 0.5 秒 to 1 second depending on reading

• 精确度: 高度刻度 ±2%, 倾斜刻度 ¼"

• 刻度: 0 到 ±35mm (15m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±50mm (20m 距离刻度), 分辨率 ¼-½m

• 刻度: 0 到 ±200' (66' 距离刻度), 分辨率 1-5'

• 刻度: 0 到 ±90°, 分辨率 1°

• 刻度: 0 到 ±150%, 分辨率 1-2%

• 刻度: 0 到 ±100g, 分辨率 1 g

• 刻度: 0 到 ±1600 mils, 分辨率 10 mils